

Eliminex®/Eliminex® Combo Series







A009_0319

Mainline filters & combo filters

Protects refrigerated
dryers and shop mainlines

ELIMINEX®

**ELIMINEX®
COMBO**

Flow (SCFM)	Inlet/Outlet (NPT)	Water & Dirt 3.0 micron+	Water, Dirt, & Oil 0.01 micron+	Replacement Elements
60	1/2"	 EX104-B	 EX204-B/EX204i-B	Eliminex®: 1P-060 Eliminex® Combo: 1st: 1P-060 2nd: 3C-060
90	3/4"	 EX106	 EX206/EX206i	Eliminex®: 1P-090 Eliminex® Combo: 1st: 1P-090 2nd: 3C-090
150	1"	 EX108	 EX208/EX208i	Eliminex®: 1P-150 Eliminex® Combo: 1st: 1P-150 2nd: 3C-150

Max temperature: 125°F Max pressure: 175 PSIG

Standard with automatic drains, easy tool-less maintenance with quick disconnect clamp ring.
"i" denotes filters that are supplied with Differential Pressure Indicators on 2nd stage coalescing filter (not shown).

CA PROPOSITION 65 WARNING



WARNING: Cancer and
Reproductive Harm

www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

