

STEALTH unit



Features & Benefits

- Great final polishing filter and control unit
- Quick disconnect clamp ring design
- 0.01 micron at 99.99998% efficiency
- Spin-on/spin-off element
- Equipped with brass petcock manual drain
- Comes with high flow regulator/gauge
 - 1/4" On STEALTH 7000
 - 3/8" On STEALTH 7030
- 0-160 PSI gauge with glass lens
- Cleaner compressed air with no oil to your applications
- Simple design requires no tools for maintenance
- Easy service of elements
- Extremely long element life
- 99.99998% effective at oil removal

Specifications

- Replacement Element: 3C-060
- Max. Air Pressure: 200 PSIG
- Max. Operating Temp: 125° F
- Max. Flow: 60 SCFM @ 100 PSI
- 1/2" NPT inlet,
1/4" Outlet: 7000, 3/8": 7030
- 1/2" Ball Valve: BV-051

Applications

- After Filter for Refrigerated Dryer
- After Filter for Desiccant Dryer
- Final Paint Air Filter and Control Unit

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm

www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe



Removes: ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



- 1/4"** **STEALTH 6900B** No Regulator, 1/2" NPT ports
- STEALTH 6950B** Regulator w/ Gauge
- STEALTH 6952B** Regulator w/ Gauge, (2) 1/4" Outlets
- 3/8"** **STEALTH 3050B** Regulator w/ Gauge
- STEALTH 3052B** Regulator w/ Gauge, (2) 3/8" Outlets

Removes: ● ● ●

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



- 1/4"** **STEALTH 6910B** No Regulator, 1/2" NPT ports
- STEALTH 6960B** Regulator w/ Gauge
- STEALTH 6962B** Regulator w/ Gauge, (2) 1/4" Outlets
- 3/8"** **STEALTH 3060B** Regulator w/ Gauge
- STEALTH 3062B** Regulator w/ Gauge, (2) 3/8" Outlets

Removes: ● ●

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



- 1/4"** **STEALTH 7000B** Regulator w/ Gauge
- STEALTH 7800B** No Regulator, 1/2" NPT ports
- 1/2"** **STEALTH 1000B** Regulator w/ Gauge
- STEALTH 1500B** Regulator w/ Gauge and manifold
- STEALTH 1700B** Regulator w/ Gauge and manifold
- STEALTH 3250B** Regulator w/ Oversized Gauge/manifold
- 3/8"** **STEALTH 7030B** Regulator w/ Gauge

Removes: ● ● ●

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain
2nd Stage: Brass Manual Petcock Drain



- 1/2"** **STEALTH 6062B** Regulator w/ Gauge and manifold
- 3/8"** **STEALTH 6060B** Regulator w/ Gauge
- 3/4"** **STEALTH 7500** Regulator w/ Gauge, no bracket

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key: ● Water ● Dirt ● Oil

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov/product



(800) 521-9200

www.driair.com | www.rti-pbe.com

@RTiPBE

@rti_pbe

