

## STEALTH unit



### Features and Benefits

- Inverse-Flow® Technology with 3½" filter depth
- Quick disconnect clamp ring design
- 1.0 micron final filtration
- Spin-on/spin-off element
- High flow ¾" regulated outlet now available
- Equipped with brass petcock manual drain
- Rated for 60 SCFM
- Available with activated carbon for oil removal
- Non-corrosive internal metal
- Pressure regulator/gauge standard
- Cleaner compressed air with no oil to your applications
- Simple design requires no tools for maintenance
- Easy service of elements
- Extremely long element life
- 99.99998% effective at oil removal with activated carbon

### Specifications

- Replacement Element: 6950-1
- Max. Air Pressure: 150 PSIG
- Max. Operating Temp: 125° F
- Max. Flow: 60 SCFM @ 100 PSI
- ½" NPT Inlet
- ¾" NPT Regulated Outlet
- ½" Brass Ball Valve - BV-051

### Applications

- Air Tools, Sand Blasting, Sanding Impacts, Buffing
- Ideal for Mechanical Section of Shop

CA PROPOSITION 65 WARNING



**WARNING:** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)



(800) 521-9200



[www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)



@RTiPBE



@rti\_pbe



Removes:  

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



<b>1/4"</b>	<b>STEALTH 6900B</b>	No Regulator, 1/2" NPT ports
	<b>STEALTH 6950B</b>	Regulator w/ Gauge
	<b>STEALTH 6952B</b>	Regulator w/ Gauge, (2) 1/4" Outlets
<b>3/8"</b>	<b>STEALTH 3050B</b>	Regulator w/ Gauge
	<b>STEALTH 3052B</b>	Regulator w/ Gauge, (2) 3/8" Outlets

Removes:   

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



<b>1/4"</b>	<b>STEALTH 6910B</b>	No Regulator, 1/2" NPT ports
	<b>STEALTH 6960B</b>	Regulator w/ Gauge
	<b>STEALTH 6962B</b>	Regulator w/ Gauge, (2) 1/4" Outlets
<b>3/8"</b>	<b>STEALTH 3060B</b>	Regulator w/ Gauge
	<b>STEALTH 3062B</b>	Regulator w/ Gauge, (2) 3/8" Outlets

Removes:  

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



<b>1/4"</b>	<b>STEALTH 7000B</b>	Regulator w/ Gauge
	<b>STEALTH 7800B</b>	No Regulator, 1/2" NPT ports
<b>1/2"</b>	<b>STEALTH 1000B</b>	Regulator w/ Gauge
	<b>STEALTH 1500B</b>	Regulator w/ Gauge and manifold
	<b>STEALTH 1700B</b>	Regulator w/ Gauge and manifold
	<b>STEALTH 3250B</b>	Regulator w/ Oversized Gauge/manifold
<b>3/8"</b>	<b>STEALTH 7030B</b>	Regulator w/ Gauge

Removes:   

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain  
2nd Stage: Brass Manual Petcock Drain



<b>1/2"</b>	<b>STEALTH 6062B</b>	Regulator w/ Gauge and manifold
<b>3/8"</b>	<b>STEALTH 6060B</b>	Regulator w/ Gauge
<b>3/4"</b>	<b>STEALTH 7500</b>	Regulator w/ Gauge, no bracket

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key:  Water  Dirt  Oil

CA PROPOSITION 65 WARNING



**WARNING:** Cancer and Reproductive Harm

[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)



(800) 521-9200



[www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)



@RTiPBE



@rti\_pbe

