

STEALTH unit



Features and Benefits

- Inverse-Flow® Technology with 3½" filter depth
- Quick disconnect clamp ring design
- 1.0 micron final filtration
- Spin-on/spin-off element
- Now featuring ¾" outlet
- Equipped with brass petcock manual drain
- Rated for 60 SCFM
- Removes oil contaminants as well as dirt & water
- Non-corrosive internal metal
- Pressure regulator/gauge standard
- Cleaner compressed air with no oil to your applications
- Simple design requires no tools for maintenance
- Easy service of elements
- Extremely long element life
- 99.99998% effective at oil removal with activated carbon

Specifications

- Replacement Element: 6960-1
- Max. Air Pressure: 150 PSIG
- Max. Operating Temp: 125° F
- Max. Flow: 60 SCFM @ 100 PSI
- ½" Inlet
- ¾" Regulated Outlet
- ½" Ball Valve: BV-051

Applications

- Air Tools, Sand Blasting, Sanding Impacts, Buffing
- Ideal for Mechanical Section of Shop

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe



Removes:  

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"	STEALTH 6900B	No Regulator, 1/2" NPT ports
	STEALTH 6950B	Regulator w/ Gauge
	STEALTH 6952B	Regulator w/ Gauge, (2) 1/4" Outlets
3/8"	STEALTH 3050B	Regulator w/ Gauge
	STEALTH 3052B	Regulator w/ Gauge, (2) 3/8" Outlets

Removes:   

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"	STEALTH 6910B	No Regulator, 1/2" NPT ports
	STEALTH 6960B	Regulator w/ Gauge
	STEALTH 6962B	Regulator w/ Gauge, (2) 1/4" Outlets
3/8"	STEALTH 3060B	Regulator w/ Gauge
	STEALTH 3062B	Regulator w/ Gauge, (2) 3/8" Outlets

Removes:  

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"	STEALTH 7000B	Regulator w/ Gauge
	STEALTH 7800B	No Regulator, 1/2" NPT ports
1/2"	STEALTH 1000B	Regulator w/ Gauge
	STEALTH 1500B	Regulator w/ Gauge and manifold
	STEALTH 1700B	Regulator w/ Gauge and manifold
	STEALTH 3250B	Regulator w/ Oversized Gauge/manifold
3/8"	STEALTH 7030B	Regulator w/ Gauge

Removes:   

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain
2nd Stage: Brass Manual Petcock Drain



1/2"	STEALTH 6062B	Regulator w/ Gauge and manifold
3/8"	STEALTH 6060B	Regulator w/ Gauge
3/4"	STEALTH 7500	Regulator w/ Gauge, no bracket

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key:  Water  Dirt  Oil

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm

www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

