

STEALTH unit



Features

- Inverse-Flow® Technology with 3½" filter depth
- Quick disconnect clamp ring design
- 1.0 micron final filtration
- Spin-on/spin-off element
- Equipped with brass petcock manual drain
- Removes oil contaminants as well as dirt & water
- Non-corrosive internal metal
- Heavy duty metal bowl construction

Applications

- Air tools, sand blasting, sanding impacts, buffing
- Ideal for mechanical section of shop

Benefits

- Cleaner compressed air with no water to your applications
- Simple design requires no tools for maintenance
- Easy service of elements
- Extremely long element life
- 99.5 % effective at water removal
- ½" BV-051 ball valve

Specifications

- Replacement Element: 6950-1
- Maximum Air Pressure: 200 PSIG
- Maximum Operating Temp: 125° F
- Maximum Flow: to 60 SCFM

CA PROPOSITION 65 WARNING



WARNING: Cancer and
Reproductive Harm
www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe



Removes:  

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



| | | |
|-------------|----------------------|--------------------------------------|
| 1/4" | STEALTH 6900B | No Regulator, 1/2" NPT ports |
| | STEALTH 6950B | Regulator w/ Gauge |
| | STEALTH 6952B | Regulator w/ Gauge, (2) 1/4" Outlets |
| 3/8" | STEALTH 3050B | Regulator w/ Gauge |
| | STEALTH 3052B | Regulator w/ Gauge, (2) 3/8" Outlets |

Removes:   

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



| | | |
|-------------|----------------------|--------------------------------------|
| 1/4" | STEALTH 6910B | No Regulator, 1/2" NPT ports |
| | STEALTH 6960B | Regulator w/ Gauge |
| | STEALTH 6962B | Regulator w/ Gauge, (2) 1/4" Outlets |
| 3/8" | STEALTH 3060B | Regulator w/ Gauge |
| | STEALTH 3062B | Regulator w/ Gauge, (2) 3/8" Outlets |

Removes:  

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



| | | |
|-------------|----------------------|---------------------------------------|
| 1/4" | STEALTH 7000B | Regulator w/ Gauge |
| | STEALTH 7800B | No Regulator, 1/2" NPT ports |
| 1/2" | STEALTH 1000B | Regulator w/ Gauge |
| | STEALTH 1500B | Regulator w/ Gauge and manifold |
| | STEALTH 1700B | Regulator w/ Gauge and manifold |
| | STEALTH 3250B | Regulator w/ Oversized Gauge/manifold |
| 3/8" | STEALTH 7030B | Regulator w/ Gauge |

Removes:   

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain
2nd Stage: Brass Manual Petcock Drain



| | | |
|-------------|----------------------|---------------------------------|
| 1/2" | STEALTH 6062B | Regulator w/ Gauge and manifold |
| 3/8" | STEALTH 6060B | Regulator w/ Gauge |
| 3/4" | STEALTH 7500 | Regulator w/ Gauge, no bracket |

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key:  Water  Dirt  Oil

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm

www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

