

STEALTH unit



Specifications

- Maximum flow: 60 SCFM at 100 PSI
- Activated carbon 1st stage element removes oil to 0.003 PPM
- Two (2) 1/2" regulated exhaust ports
- Final filtration to 0.01 micron at 99.99998% efficiency
- Maximum pressure: 150 PSI, maximum temp: 125° F
- High flow 1/2" regulator/gauge, 0-160 PSI gauge
- 1/2" NPT inlet, 3/8" NPT outlet
- Multiport manifold, two (2) HFMC-1 couplers, and mounting brackets
- Automatic drain in 1st stage, manual petcock drain in 2nd stage

Benefits

- Inverse-Flow® Technology
- Water, dirt, and oil removal
- Auto drain 1st stage
- Easy serviceability (no tools needed!)
- Snap-lock ring design
- Easy spin-on/spin-off design
- Heavy duty metal construction

Applications

- Paint booths
- Lacquer spraying
- Critical air tools
- Prep stations

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm

www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe



Removes:  

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"	STEALTH 6900B	No Regulator, 1/2" NPT ports
	STEALTH 6950B	Regulator w/ Gauge
	STEALTH 6952B	Regulator w/ Gauge, (2) 1/4" Outlets
3/8"	STEALTH 3050B	Regulator w/ Gauge
	STEALTH 3052B	Regulator w/ Gauge, (2) 3/8" Outlets

Removes:   

1.0 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"	STEALTH 6910B	No Regulator, 1/2" NPT ports
	STEALTH 6960B	Regulator w/ Gauge
	STEALTH 6962B	Regulator w/ Gauge, (2) 1/4" Outlets
3/8"	STEALTH 3060B	Regulator w/ Gauge
	STEALTH 3062B	Regulator w/ Gauge, (2) 3/8" Outlets

Removes:  

0.01 micron • 60 SCFM • Brass Manual Petcock Drain



1/4"	STEALTH 7000B	Regulator w/ Gauge
	STEALTH 7800B	No Regulator, 1/2" NPT ports
1/2"	STEALTH 1000B	Regulator w/ Gauge
	STEALTH 1500B	Regulator w/ Gauge and manifold
	STEALTH 1700B	Regulator w/ Gauge and manifold
	STEALTH 3250B	Regulator w/ Oversized Gauge/manifold
3/8"	STEALTH 7030B	Regulator w/ Gauge

Removes:   

0.01 micron • 60 SCFM • 1st Stage: Automatic Float Drain
2nd Stage: Brass Manual Petcock Drain



1/2"	STEALTH 6062B	Regulator w/ Gauge and manifold
3/8"	STEALTH 6060B	Regulator w/ Gauge
3/4"	STEALTH 7500	Regulator w/ Gauge, no bracket

Note: All Stealth units feature 1/2" NPT Inlet, Max Pressure: 200 PSI, Max Temp: 125°F | Removal Key:  Water  Dirt  Oil

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm

www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

