

# BRAD-PERF-25/50

A062\_0620

Clean, dry spray and breathing air supply

## Features & Benefits

- Consistent less than -40°F dew point to the gun
- Delivers perfectly clean, dry air for flawless finishes every time
- Has the most activated carbon of any competitive breathing/paint air system on the market
- Engineered for use with all paint spray guns (not included), especially HVLP guns
- Supplies Grade D Breathing Air
- BRAD-PERF-25C for single gun spraying;  
BRAD-PERF-50C for two gun spraying booths
- Regenerative desiccant beads require little maintenance
- Monitor design is directly inline with the air flow ensuring consistent, safe monitoring
- Self calibrating monitor w/audible alarm
- Monitor displays actual CO levels & alarms at 10ppm of CO



**BRAD-PERF-50C**

## You Pick The Operator Kit: (sold separately)

Optional Operator's Kit for Painter



**BRAD-OK**

Optional Operator's Kit for Painter



**BRAD-OK-M2C-50**

CA PROPOSITION 65 WARNING



**WARNING:** Cancer and  
Reproductive Harm

[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)



(800) 521-9200



[www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)



@RTiPBE



@rti\_pbe



## BRAD-PERF-25C Breakdown

## BRAD-PERF-50C Breakdown

### BRAD-PC2C

RTi Patented 2 Stage  
Pre-Filters with CO Monitor



- 60/150 SCFM at 100 PSI
- 1/2" ball valve inlet
- Auto drain 1st stage
- Capacity:  
1st stage - 1 micron  
2nd stage - 0.01 micron  
at 99.9998% efficiency

- Power Pack with battery Back-up supplied with monitor
- Replacement Elements:  
1st stage: DE362C  
2nd stage: 3C-151

Both 25 & 50 Models Utilize the BRAD-PC2C

### ARAD-25

- Regenerative desiccant dryer uses dry air purge to recondition desiccant bed
- Up to 25 SCFM at 100 PSI
- -40 °F dew point
- 3/8" Inlet/outlet
- Inlet flow: 29 SCFM max
- Moisture indicator at outlet
- Uses < 0.1 Amps
- Fused overload protection
- 110 Vac w/ 5' power cord
- NEMA 4 enclosure
- Easy wall mount design
- Quiet operation
- Aluminum towers - no rust



Desiccant Dryer

### ARAD-50

- Regenerative desiccant dryer uses dry air purge to recondition desiccant bed
- Up to 50 SCFM at 100 PSI
- -40 °F dew point
- 3/8" Inlet/outlet
- Inlet flow: 54 SCFM max
- Moisture indicator at outlet
- Uses < 0.1 Amps
- Fused overload protection
- 110 Vac w/ 5' power cord
- NEMA 4 enclosure
- Easy wall mount design
- Quiet operation
- Aluminum towers - no rust



### PERF-25-AF



- 60 SCFM at 100 PSI
- 1/2" Inlet/Outlet
- Capacity - .01 micron @ 99.9998% efficiency
- Eliminates desiccant dust contamination of paint
- Manual petcock drain
- 3/8" High Flow Regulator with Gauge. Part #: RG30

After Filter & Accessories

### PERF-50-AF



- 60 SCFM at 100 PSI
- 1/2" Inlet/Outlet
- Capacity - .01 micron @ 99.9998% efficiency
- Eliminates desiccant dust contamination of paint
- Manual petcock drain
- 1/2" High Flow Regulator with Gauge. Part #: NAR4000-NO4 and PG-160

**Note:**  
Regulator & gauge sold separately when ordering "-AF", but is included in "PERF-25"/"PERF-50" complete package

CA PROPOSITION 65 WARNING



**WARNING:** Cancer and Reproductive Harm

[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)



(800) 521-9200



[www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)



@RTiPBE



@rti\_pbe

