

## 3-Stage filter with heavy duty regulator and multiport manifold



### Features & Benefits

- 3-stage filter with 1/2" regulator, multiport manifold, two HFMC-1 couplers, and two BK-1 mounting brackets
- Auto drain on first stage
- Brass manual petcock drain on second and third stages
- **First Stage:** charcoal (carbon) removes hydrocarbons, water, dirt, and oil  
**Second Stage:** removes fine particulates  
**Third Stage:** provides a finer level of filtration
- Provides Grade 'D' breathing air for spraying applications (with monitor)
- All metal, corrosion-resistant anodized aluminum body on the regulator
- Tee handle knob, relieving type regulator

### Specifications

*Max. Pressure* 200 PSIG  
*Filter Capacity* 0.01 micron at 99.99998% efficiency

*Flow Capacity* 60 SCFM at 100 PSI  
*Max. Operating Temp.* 125°F

*Replacement Elements:*  
1st Stage 4P-060  
2nd Stage 3C-060  
3rd Stage 3C-061

*Weight* 12 lbs.  
*Height* 10.5"  
*Length* 22"  
*Depth* 3.5"

CA PROPOSITION 65 WARNING



**WARNING:** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)

