

BRAD-BD1

A086_0120

Breathing air system

BRAD-BD1

Pre-filter Combo, CO Monitor,
½" Regulator with 0-160 PSI Gauge

Replacement Element Kit: BRAD-01C-MK

1-2 Operators

Pre-filter Combo & CO Monitor

BRAD-CM3

- Preset at 10 ppm for CO alarm
- Has bar graph display
- Comes with calibration magnet for calibration
- 115 volts AC electric plug connection
- Low pressure alarm (can be bypassed)
- Has RF signal 10 second delay to eliminate false alarms

Replacement Elements

- First Stage: 4P-060
- Second Stage: 3C-061



available on stand: BRAD-BD1-PRO

Features

- Monitors Grade "D" breathable air
- Ultra lightweight design, 1-2 Operators
- Deep bed activated carbon pre-filter for hydrocarbon removal to 0.003 ppm
- 0.01 micron final filter designed for fine particulate and oil removal at 99.9998% efficiency
- Dual ½" outlets with ¼" high flow quick disconnects provided
- Rated for up to 60 scfm
- Heavy duty, high flow regulator assembled with FDA lubricant
- 0-60 PSIG mini-regulator controls air pressure to monitor
- Low air sample rate through monitor
- 110 Volt AC electrical
- Assembly is supplied mounted on ¾" board for easy installation

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm

www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

