

Reciprocating Piston Compressors

Ai001_0918

5, 7.5, 10, and 15 horsepower compressors

Features & Benefits

- Heavy duty two stage solid cast iron pump
- Disk and spring valves
- Bearings on both ends of the crank shaft
- Needle bearings, inserts on rods
- Industrial grade electric motor
- ASME tested powder coated steel tank
- 2 groove B width motor pulley
- All UL electrical controls
- Access to compressor valves without compressor head removal
- Auto start/stop
- Fully enclosed belt guard
- Heavy duty air filter
- Torrington needle bearings
- Magnetic starter mounted and wired
- Centrifugal unloader
- Stainless steel flex air lines
- TEFC drive motor (3 phase only)
- Free freight included on elite models



Air cooled after cooler on Elite units.

Order Guide

Part Number	Phase	HP	Voltage	Tank size	Length (in.)	Width (in.)	Height (in.)
PV-815-20-B	1	5	208-230	80 gallon, vertical	32.0	26.0	78.0
PH-835-20-B	3	5	208-230-460	80 gallon, horizontal	63.0	24.0	45.0
PV-817.5-25-B	1	7.5	208-230	80 gallon, vertical	32.0	26.0	78.0
PH-837.5-25-B	3	7.5	208-230-460	80 gallon, horizontal	63.0	24.0	45.0
PV-1217.5-25-B	1	7.5	208-230	120 gallon, vertical	42.0	34.0	84.0
PH-1237.5-25-B	3	7.5	208-230-460	120 gallon, horizontal	70.0	26.0	45.0
PV-8110-37-B	1	10	208-230	80 gallon, vertical	36.0	24.0	74.0
PH-8310-37-B	3	10	208-230-460	80 gallon, horizontal	64.0	24.0	48.0
PV-12110-37-B	1	10	208-230	120 gallon, vertical	42.0	34.0	84.0
PH-12310-37-B	3	10	208-230-460	120 gallon, horizontal	70.0	26.0	45.0
PH-12315-41-B	3	15	208-230-460	120 gallon, horizontal	70.0	26.0	54.0
PH-24315-58-B	3	15	208-230-460	240 gallon, horizontal	85.0	30.0	60.0

For Elite versions, add 'E' instead of 'B'. | For more sizes and options, call factory.

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

