

Cube Compressors - Rotary Screw

Ai004_0918

5, 7.5, and 10 horsepower compressors

Features & Benefits

- Maximum operating pressure up to 190 psi (Standard max operating pressure 150 psi)
- Low tip speed on air end for long life
- Less than 3ppm oil carry over
- Single solenoid operation
- Spin on separator
- Spin on oil filter
- Air/Oil Cooler
- Vibration isolation pads
- 8000hr full synthetic fluid
- Analog easy to use controls
- Heavy duty air filter
- Self tensioning drive belt system
- 10 minute timed shut down for electrical savings
- Minimal floor space foot print
- Industrial duty electric drive motor
- EZ access belt guard
- High air temperature sensor
- High oil temperature sensor
- High pressure sensor
- Free freight included on elite models



Order Guide

Part Number	Phase	HP	Voltage	Length (in.)	Width (in.)	Height (in.)	Weight (lb.)
RSQ15-17-EVB	1	5	208-230	28.0	30.0	40.0	345
RSQ35-17-EVB	3	5	208-230 / 460-480	28.0	30.0	40.0	345
RSQ17-26-EVB	1	7.5	208-230	28.0	30.0	40.0	345
RSQ37-26-EVB	3	7.5	208-230 / 460-480	28.0	30.0	40.0	345
RSQ110-36-EVB	1	10	208-230	28.0	30.0	40.0	345
RSQ310-39-EVB	3	10	208-230 / 460-480	28.0	30.0	40.0	345
RSQ315-52-EVB	3	15	208-230 / 460-480	28.0	30.0	40.0	345

For Elite versions, add 'E' instead of 'B'. | For more sizes and options, call factory.

CA PROPOSITION 65 WARNING



WARNING: Cancer and Reproductive Harm
www.P65Warnings.ca.gov/product



(800) 521-9200



www.driair.com | www.rti-pbe.com



@RTiPBE



@rti_pbe

