

# GCU Rotary Screw Compressors

Ai008\_0918

7.5, 10, and 20 horsepower compressors

## Features & Benefits

- Spin on separator
- Spin on oil filter
- Simplified operating controls (no complicated micro-processor)
- Single control solenoid operation
- UL control components
- Alpha profile rotors
- Air/oil cooler
- Easy to remove bolt on oil cooler
- Standard operating pressure of 175 PSI
- Extended oil drain for easy service
- Factory filled with premium synthetic fluid
- ASME/CRN powder coated receiver
- Heavy duty air filter
- Automotive tank drain
- Smart contractor
- Vibration isolation pads
- Tank discharge ball valve
- TEFC drive motor (in 3 phase only)
- Free freight included on elite models



## Order Guide


Part Number	Phase	HP	Voltage	Tank size	Length (in.)	Width (in.)	Height (in.)
RSB17-28-GE	1	7.5	208-230	80 gallon, vertical	25.0	25.0	78.0
RSB37-28-GE	3	7.5	208-230 / 460-480	80 gallon, vertical	25.0	25.0	78.0
RSB110-36-GE	1	10	208-230	80 gallon, vertical	36.0	25.0	78.0
RSB310-38-GE	3	10	208-230 / 460-480	80 gallon, vertical	36.0	25.0	78.0
RSB320-78-GE	3	20	208-230 / 460-480	120 gallon, horizontal	72.0	36.0	50.0

CA PROPOSITION 65 WARNING



**WARNING:** Cancer and Reproductive Harm  
[www.P65Warnings.ca.gov/product](http://www.P65Warnings.ca.gov/product)



 (800) 521-9200

 [www.driair.com](http://www.driair.com) | [www.rti-pbe.com](http://www.rti-pbe.com)

 @RTiPBE

 @rti\_pbe

